

16 mm GEN NEXT LED INDICATORS

- > Sleek & Integral Design
- > Special fire retardant plastic used
- > Easy mounting & wiring
- > Uniform & Bright Illumination
- > Operating life more than 0.1 million Burning hrs
- > Wide Voltage range
- > Available in 6 different colours
- > Withstand 2 KV surge test & passes 1.5 KV HV test for 60 seconds
- > Inbuilt IP20 protection for terminals & IP65



16mm LED Indicator

Cat. No. : SIL□□□□□

Colour (4th Digit) : **R** **G** **Y** **W** **B** **A**

Voltage (5th, 6th, 7th & 8th Digit):

012 C - 12 V AC/DC
024 C - 24 V AC/DC
048 C - 48 V AC/DC
064 C - 64 V AC/DC
110 A - 110 V AC/DC
240 A - 240 V AC

22.5 mm GEN NEXT LED INDICATORS

- > Gen Next LED Indicator with SMD LED technology
- > New sleek and compact design
- > Lug wiring possible
- > Uniform & bright illumination
- > Wide voltage range
- > Operating life more than 0.1 million Burning hrs
- > Can be assembled in push button stations
- > Integrated IP 20 protection for terminals & IP 65 protection
- > Passes surge test of 2 KV & HV test of 1.5KV
- > **CE & UL** approved



Gen Next LED Indicator

Cat. No. : EIL□□□□□

Colour (4th Digit) : **R** **G** **Y** **W** **B** **A**

Voltage (5th, 6th, 7th & 8th Digit):

012 C - 12 V AC/DC
024 C - 24 V AC/DC
048 C - 48 V AC/DC
064 C - 64 V AC/DC
110 A - 110 V AC
110 D - 110 V DC
240 A - 240 V AC
220 D - 220 V DC

Note: Colours available - R - Red, G - Green, Y - Yellow, W - White/Opal, B - Blue, A - Amber